

TEMPERATURE CONTROLLER PRODUCT CATALOG

温度控制器产品目录





Model	Size	Specifications
PMA100	48*48MM	MAX 50 segments programmable LCD display, high brightness backlight screen, wide viewing angle. Input type:TC/RTD (K,J,E,T,S,PT100,Cu100,Cu50,It can switch in menu) Analog signals:0-5V,0-10V,1-5V,4-20mA (customizable) Output type: SSR/Relay/ 0-10V /4-20mA Alarm : 1 / 2 RS485 :YES/NO
PMA400	48*96MM	
PMA700	72*72MM	
PMA900	96*96MM	

The name of the series	Code name	Panel size	Code name	Main control output	Code name	Group 2 output	Code name	Alarm output	Code name	Transfer the output	Code name	Remote control input	Code name	communication	Code name	The input signal	Code name	The main power supply	Code name
Constant value control	MA	DIN48x48	100	no output	0	no output	0	No alarm	0	No transfer	0	nothing	0	nothing	0	thermocouple	1	85~265V	A
Program control	PMA	DIN72x72	700	Relay contact output	1	Relay contact output	1	A set of alarm	1	PV value transfer	1			24V auxiliary power supply	1	Platinum resistance	2		
		DIN48x96	400	SSR trigger signal	2	SSR trigger signal	2	Two groups of alarm	2	SV value transfer	2			TTL main control	3	Linear signal	3		
		DIN96x96	900	4~20mA current output	3	4~20mA	3							RS485 MODBUS	B				
				0~10V voltage output	4	0~10V	4												
				Single phase SCR zero trigger	5														
				Three phase SCR zero trigger	6														
				No proportional feedback motor	7														
				Single phase zero trigger	8														
				Three phase zero trigger	9														